

erkat | rotation units

The **ERU SERIES** from Erkat represents a new generation of rotation units specifically designed for heavy duty tunnelling, trenching and concrete renovation applications. Continuous, infinite, rotation allows the drum cutter to be correctly aligned for every cutting requirement. Rotation units are fitted with a hydraulic swivel joint as standard, allowing continuous and infinite rotation without fouling hydraulic hoses.



features

long lasting, robust worm gear and housing for drum cutters in tunnelling and trenching applications

worm gears made to tight tolerances

worm gear wheel made from top quality steel

robust bearings

hydraulic swivel joint capable of passing up to 400 l/min

continuous and infinite rotational capability

compact and low maintenance

very high locking torque

2 hydraulic motors are standard on size 3 and higher

benefits

- up to 50% increased productivity in tunnelling and trenching applications
- improved accuracy when cutting wall surfaces
- quicker and more economical profiling of tunnels
- improved positioning of the cutter head reduces stress on the excavator through smoother cutting operation
- smoother cutting action results in lower pick consumption
- indexing the cutter head enables smaller trench widths
- lower costs arising from worn hydraulic hoses


Standard Erkat drum cutters can be fitted with Erkat **ERU** rotation units. Erkat rotation units can also be used with other makes of drum cutter.



Used in foundation application

erkat revolving rotation drum cutters

The new generation, **ERC** drum cutters from Erkat consists of standard, proven rotary drum cutters with integrated rotation units. There are 10 models in the range, suitable for excavators from 2 to 50 tons weight.



SERIES ERC for excavators from 2 to 50 tons	Unit	ERC 50	ERC 100	ERC 250	ERC 600	
Cutter drum diameter (A)	mm	225	320	400	575	
Cutter head width (B)	mm	480	550	620	780	
Recommended oil flow cutter	l/min	38	62	90	150	
Max. Torque at 350 bar	Nm	1.419	3.115	5.200	10.400	
Cutting force at 350 bar	N	1.2613	19.469	26.000	36.174	
Approx. Weight	kg	295	450	590	1.280	
Recommended excavator weight	tons	2 - 3	4 - 8	8 - 12	10 - 20	
Rotation Unit	Тур	ERU 1	ERU 2	ERU 2	ERU 3	

applications



Tunneling applications





ERC 650	ERC 650 P	ERC 1200	ERC 1500 X	ERC 1500 XL	ERC 2000
575	540	650	670	670	680
800	1066	850	850	1.000	1.200
190	190	300	300	300	370
13.300	12.466	23.400	23.400	23.400	33.500
46.261	46.170	72.000	72.000	72.000	98.529
1.580	1.800	2.620	2.620	2.720	3.100
15 - 25	15 - 25	20 - 40	20 - 40	20 - 40	30 - 50
ERU 4	ERU 4	ERU 5	ERU 5	ERU 5	ERU 6

applications








Trenching applications







The **ERU** range of rotation units consists of 6 models for excavator weights from 2 to 50 tons.

OFFICE FRU								
SERIES ERU for excavators from 2 to 50 tons	Unit	ERU 1	ERU 2	ERU 3	ERU 4	ERU 5	ERU 6	
Housing Diameter (A)	mm	292	367	456	567	610	700	
Total Height Incl. Hydraulic Swivel Joint (B)	mm	415	450	520	600	636	620	
Length (D)	mm	530	640	760	770	780	910	
Width (E)	mm	370	450	600	700	770	800	
Approx. Weight	kg	125	200	440	700	900	1.000	
Max. Oil Flow	l/min	10	10	30	40	40	40	
Operating Pressure	bar	160	160	160	160	160	160	
Max. Locking Torque	Nm	6.300	11.100	44.700	95.000	200.000	270.000	
Number of hydraulic motors	pcs	1	1	2	2	2	2	
Recommended excavator weight	tons	2 - 4	5 - 12	13 - 20	15 - 25	25 - 40	30 - 50	
Recommended Erkat drum cutter	type	ER 50	ER 250	ER 600	ER 650	ER 1200 ER 1500 X ER 1500 XL	ER 1500 XL ER 2000	

applications





Tunnelling and wall profiling applications




trenching the world



Erkat has a worldwide network consisting of distributors and subsidiaries. For more information, please contact Mr. Ertmer at +49 3695 60 34 66

www.erkat.de



This catalogue is used to describe our products and the accessories. The information contained in it does not imply any certified properties or indicate any suitability for certain or assumed purposes. Technical changes are reserved without prior announcement. We disclaim any liability arising from the illustrations and information in the catalogue and from all our representatives.

erkat | spezialmaschinen | service | gmbh

jeremiasstraße 4 d-36433 leimbach

germany

phone +49 (0) 3695 60 34 66 +49 (0) 3695 60 34 67 fax info@erkat.de internet www.erkat.de

erkat | spezialmaschinen | service | gmbh service | production

ulmenstraße 3 d-36469 hämbach

germany

phone +49 (0) 3695 60 34 66 +49 (0) 3695 60 34 67 fax e-mail info@erkat.de internet www.erkat.de



